

**Import Applications** (complete engine sets)

<b>Acura RSX / TSX K20 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20411.216	Dual Spring	29.4 mm	16.9 mm	82 lbs @ 40.5 mm	238 lbs @ 27mm	13.5 mm	25.3 mm

<b>Acura NSX C30 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20402.224	Dual Spring	29.3 mm	16.8 mm	80 lbs @ 36.4 mm	226 lbs @ 23.4mm	13.00 mm	21.9 mm

<b>Acura Integra B18 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20401.216	Dual Spring	29.3 mm	16.8 mm	78 lbs @ 33.40 mm	212 lbs @ 21.40 mm	12.0 mm	18.80 mm

<b>BMW E36 330 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20454.224	Dual Spring	29.6 mm	16.8 mm	70 lbs @ 40 mm	203 lbs @ 29 mm	14.5 mm	23.8 mm

<b>BMW E46 M3 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20455.224	Dual Spring	27.1 mm	19.9 mm	70 lbs @ 40 mm	200 lbs @ 29 mm	14.0 mm	24.7 mm

<b>BMW Mini 1.6 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20463.116	Single Spring	26.0 mm	17.6 mm	80 lbs @ 43 mm	212 lbs @ 33 mm	11.0 mm	30.7 mm

<b>Honda SI (99-00), Del Sol (93-97) B18 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20401.216	Dual Spring	29.3 mm	16.8 mm	78 lbs @ 33.40 mm	212 lbs @ 21.40 mm	12.0 mm	18.80 mm

**Import Applications** (complete engine sets)

<b>Honda Civic R / Civic SI / S2000 K20 / F20 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20411.216	Dual Spring	29.4 mm	16.9 mm	82 lbs @ 40.5 mm	238 lbs @ 27.0mm	13.5 mm	25.3 mm

<b>Honda Prelude H22 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20402.224	Dual Spring	29.3 mm	16.8 mm	80 lbs @ 36.4 mm	226 lbs @ 23.40 mm	13.00 mm	21.9 mm

<b>Infiniti G35 3.5L Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20452.124	Single Spring	24.8 mm	17.6 mm	65 lbs @ 38.0 mm	175 lbs @ 24.5 mm	13.5 mm	22.9 mm

<b>Lotus Elise, Exige 2ZZ Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20407.116	Single Spring	22.5 mm	15.7 mm	48 lbs @ 39.4 mm	147 lbs @ 26.9 mm	12.5 mm	25.0 mm

<b>Mazda Miata 1.8L Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20410.116	Single Spring	25.7 mm	18.1 mm	66 lbs @ 39 mm	200 lbs @ 27.0 mm	12.0 mm	24.2 mm
20432.216 *	Dual Spring	26.6 mm	14.2 mm	75 lbs @ 35.8 mm	210 lbs @ 24.1 mm	11.7 mm	22.1 mm

\*Spec Miata Race Spring, use Mazda retainer B6N7-12-123C B6N7-12-113

<b>Mazda 3 / 6 2.0L / 2.3L 16V Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
25407.116	Conical Spring	24.8 mm	18.0 mm	47 lbs @ 35.0 mm	140 lbs @ 23.50 mm	11.50 mm	21.60 mm

**Import Applications** (complete engine sets)

<b>Mitsubishi EVO VIII Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
25430.116	Conical Spring	26.0 mm	19.1 mm	85 lbs @ 38.1 mm	202 lbs @ 26.1 mm	12.00 mm	24.30 mm

<b>Nissan 350Z 3.5L Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20452.124	Single Spring	24.8 mm	17.6 mm	65 lbs @ 38.0 mm	175 lbs @ 24.5 mm	13.5 mm	22.9 mm

<b>Nissan SR20 DET Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20466.216	Double Spring	29.20 mm	21.00 mm	82 lbs @ 39.00 mm	216 lbs @ 27.50 mm	11.50 mm	25.50 mm

<b>Porsche 911 Air Cooled Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20701.212	Dual Spring	31.6 mm	17.6 mm	55 lbs @ 36.5 mm	183 lbs @ 25.5 mm	11.0 mm	20.5 mm
20444.212	High Lift Spring	31.75 mm	17.3 mm	90 lbs @ 36.0 mm	277 lbs @ 23.30 mm	12.7 mm	20.7 mm

<b>Porsche 996 GT3 / Turbo Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20453.224	Double Spring	29.60 mm	17.00 mm	70 lbs @ 32.50 mm	225 lbs @ 18.50 mm	14.00 mm	16.80 mm

<b>Subaru Impreza WRX / Sti Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20457.116	Single Spring	26.7 mm	19.10 mm	62 lbs @ 36.0 mm	175 lbs @ 25.0 mm	11.0 mm	23.2 mm

<b>Toyota Corolla, Matrix, Celica GT, MR2 Spider 1ZZ Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20409.116	Single Spring	22.2 mm	16.2 mm	39 lbs @ 33.4 mm	97 lbs @ 22.4 mm	11.0 mm	20.6 mm

**Import Applications** (complete engine sets)

<b>Toyota Corolla, Matrix, Celica GT-S 2ZZ Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20407.116	Single Spring	22.5 mm	15.7 mm	48 lbs @ 39.4 mm	147 lbs @ 26.9 mm	12.5 mm	25.0 mm

<b>VW Golf / Jetta / Passat 2.0L 8V Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20406.208	Dual Spring	30.2 mm	17.9 mm	74 lbs @ 31.75 mm	189 lbs @ 20.25 mm	11.50 mm	16.1 mm

<b>VW Golf / Jetta / Passat VR6 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20406.212	Dual Spring	30.2 mm	17.9 mm	74 lbs @ 31.75 mm	189 lbs @ 20.25 mm	11.50 mm	16.1 mm

**Domestic Applications** (complete engine sets)

<b>Chevrolet Camaro / Corvette LS1 / LS6 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
25408.116	Conical Spring	1.25	0.89	135 lbs @ 1.80	288 lbs @ 1.20	0.60	1.11
25410.116	Conical Spring	1.25	0.89	166 lbs @ 1.80	388 lbs @ 1.20	0.56	1.18

<b>Chevrolet 262 – 400 V8 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20415.116	Single Spring	1.23	0.875	92 lbs @ 1.70	213 lbs @ 1.25	0.45	1.08

<b>Chevrolet 396/402/427/454 V8 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20422.116	Single Spring	1.50	1.09	135 lbs @ 1.88	287 lbs @ 1.35	0.53	1.24

**Domestic Applications** (complete engine sets)

<b>Chrysler 318 / 340 / 360 V8 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20425.116	Single Spring	1.41	1.02	103 lbs @ 1.65	241 lbs @ 1.20	0.45	1.07

<b>Chrysler 383 / 400 / 413 / 440 V8 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20427.116	Single Spring	1.38	1.02	126 lbs @ 1.86	210 lbs @ 1.40	0.46	1.08

<b>Ford Mustang / F - Series 4.6 L Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
25409.116	Conical Spring	1.04	0.74	84 lbs @ 1.57	202 lbs @ 1.02	0.55	0.95

<b>Ford Mustang 4.6 / 5.4 32V Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
25414.132	Conical Spring	1.06	0.75	76 lbs @ 1.42	223 lbs @ 0.95	0.47	0.82

<b>Pontiac Firebird / GTO LS1 / 6 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
25408.116	Conical Spring	1.25	0.89	135 lbs @ 1.80	288 lbs @ 1.20	0.60	1.11
25410.116	Conical Spring	1.25	0.89	166 lbs @ 1.80	388 lbs @ 1.20	0.56	1.18

**Motorcycle Applications** (complete engine sets)

<b>Harley Davidson Evolution 1450cc Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
25413.204	Dual Spring	1.38	0.71	133 lbs @ 1.78	345 lbs @ 1.28	0.50	0.96
Retainer kit included							

<b>Harley Davidson Evolution 1540cc Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
25412.204	Dual Spring	1.38	0.71	149 lbs @ 1.78	385 lbs @ 1.23	0.55	0.96
Retainer kit included							

<b>Harley Davidson Panhead / Shovel Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20433.204	Dual Spring	1.65	0.87	131 lbs @ 1.50		0.53	0.88
20434.204	Dual Spring	1.65	0.87	181 lbs @ 1.50		0.53	0.88

<b>Harley Davidson WL Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20435.104	Single Spring	0.98	0.66	92 lbs @ 1.97		0.50	1.33

<b>Yamaha YZ250F / R1 Engine</b>							
Part Number	Type	O.D.	I.D.	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
20456.102	Intake Spring	16.4 mm	11.4 mm	33 lbs @ 28 mm	74 lbs @ 22 mm	6.00 mm	19.75 mm
20458.102	Exhaust Spring	19.0 mm	11.4 mm	40 lbs @ 28 mm	107 lbs @ 22 mm	6.00 mm	19.95 mm

**Circle Track Applications**

<b>Circle Track Roller Lifter Applications</b>							
<b>Part Number</b>	<b>Type</b>	<b>O.D.</b>	<b>I.D.</b>	<b>Seat Pressure</b>	<b>Open Pressure</b>	<b>Max. Lift</b>	<b>Coil Bind</b>
30003.02	Dual Spring	1.500	0.780	229 lbs @ 1.90	547 lbs @ 1.25	0.65	1.12
30013.02	Dual Spring	1.570	0.825	187 lbs @ 2.05	546 lbs @ 1.40	0.65	1.25
30004.02	Dual Spring	1.580	0.840	243 lbs @ 1.95	627 lbs @ 1.20	0.75	1.08
30010.02	Dual Spring	1.590	0.840	220 lbs @ 2.05	712 lb @ 1.25	0.80	1.17
35003.02	Dual Spring Beehive	1.620 / 1.530	0.83 / 0.74	246 lbs @ 2.12	714 lbs @ 1.33	0.75	1.15
30005.02	Dual Spring	1.625	0.850	255 lbs @ 2.00	691 lbs @ 1.25	0.75	1.13
30012.02	Dual Spring	1.625	0.840	270 lbs @ 2.00	760 lb @ 1.25	0.75	1.16

<b>Circle Track Flat Tappet Applications</b>							
<b>Part Number</b>	<b>Type</b>	<b>O.D.</b>	<b>I.D.</b>	<b>Seat Pressure</b>	<b>Open Pressure</b>	<b>Max. Lift</b>	<b>Coil Bind</b>
30008.02	Dual Spring	1.520	0.80	190 lbs @ 2.05	584 lbs @ 1.25	0.80	1.17
30001.02	Dual Spring	1.570	0.84	203 lbs @ 2.05	579 lbs @ 1.30	0.75	1.07

<b>Circle Track Restrictor Plate Applications</b>							
<b>Part Number</b>	<b>Type</b>	<b>O.D.</b>	<b>I.D.</b>	<b>Seat Pressure</b>	<b>Open Pressure</b>	<b>Max. Lift</b>	<b>Coil Bind</b>
300007.01	Single Spring	1.54	1.12	145 lbs @ 1.90	330 lbs @ 1.35	0.55	1.24

# EVS Specification Sheet

P/N Each	Outer O.D.		Inner I.D.		L1		F1		L2		Max. Lift		F2		Lc	
	mm	inch	mm	inch	mm	inch	N	LBS	mm	inch	mm	inch	N	LBS	mm	inch
20456.01	16.4	0.65	11.4	0.45	28.0	1.10	150	34	22.0	0.87	6.0	0.24	330	74	19.8	0.78
20458.01	19.0	0.75	13	0.51	28.0	1.10	176	40	22.0	0.87	6.0	0.24	477	107	20	0.79
20439.01	20.5	0.81	15.5	0.61	32.0	1.26	98	22	18.0	0.71	14.0	0.55	310	70	15	0.59
20409.01	22.2	0.87	16.2	0.64	33.4	1.31	175	39	22.4	0.88	11.0	0.43	433	97	20.6	0.81
20407.01	22.5	0.89	15.7	0.62	39.4	1.55	212	48	26.9	1.06	12.5	0.49	655	147	25	0.98
25100.01	24.3	0.96	17.1	0.67	37.5	1.48	232	52	26.0	1.02	11.5	0.45	647	145	24.5	0.96
20452.01	24.8	0.98	17.6	0.69	38.0	1.50	289	65	24.5	0.96	13.5	0.53	775	174	22.9	0.90
20442.02	25.2	0.99	14	0.55	35.0	1.38	260	58	21.0	0.83	14.0	0.55	750	169	19.9	0.78
TRD9B5.02	25.3	0.99	13.3	0.52	33.2	1.30	316	71	22.4	0.88	10.8	0.42	870	196	21.2	0.83
20405.02	25.5	1.01	13.6	0.54	34.2	1.35	337	76	21.2	0.83	13.0	0.51	999	224	19.9	0.78
20410.01	25.6	1.01	18	0.71	39.0	1.54	292	66	27.0	1.06	12.0	0.47	886	199	24.2	0.95
20441.01	25.6	1.01	18.2	0.72	34.0	1.34	250	56	23.0	0.91	11.0	0.43	740	166	21.1	0.83
22632.02	26.0	1.02	14.4	0.57	34.8	1.37	256	58	20.8	0.82	14.0	0.55	750	169	19.5	0.77
20463.01	26.0	1.02	17.6	0.69	43.0	1.69	348	78	33.0	1.30	11.0	0.43	944	212	30.7	1.21
25409.01	26.4	1.04	18.8	0.74	39.9	1.57	375	84	25.9	1.02	14.0	0.55	897	202	24.1	0.95
25430.01	26.5	1.04	19.1	0.75	38.1	1.50	381	86	26.1	1.03	12.0	0.47	902	203	24.3	0.96
20432.02	26.6	1.05	14.2	0.56	35.8	1.41	356	80	24.1	0.95	11.7	0.46	935	210	22.1	0.87
25407.01	26.6	1.05	19.8	0.78	35.0	1.38	208	47	23.5	0.93	11.5	0.45	622	140	21.6	0.85
20457.01	26.7	1.05	19.1	0.75	36.0	1.42	275	62	25.0	0.98	11.0	0.43	780	175	23.2	0.91
25414.01	27.0	1.06	19	0.75	36.0	1.42	339	76	24.0	0.94	12.0	0.47	993	223	21.2	0.83
20455.02	27.1	1.07	14.7	0.58	40.0	1.57	309	69	29.0	1.14	11.0	0.43	887	199	24.7	0.97
20438.01	27.5	1.08	20.1	0.79	32.0	1.26	265	60	20.0	0.79	12.0	0.47	765	172	18.5	0.73
20443.02	28.0	1.10	15.6	0.61	36.5	1.44	265	60	22.5	0.89	14	0.55	890	200	19.6	0.77
20440.02	28.5	1.12	15.8	0.62	40.0	1.57	367	82	26.0	1.02	14.0	0.55	1059	238	24.3	0.96
25001.01	28.6	1.13	21.4	0.84	38.0	1.50	260	58	27.0	1.06	11.0	0.43	618	139	24.6	0.97
20430.02	29.0	1.14	21.5	0.85	34.8	1.37	394	89	20.7	0.81	14.1	0.56	1207	271	19.8	0.78
20437.02	29.2	1.15	16.6	0.65	38.0	1.50	296	67	24.0	0.94	14.0	0.55	1016	228	22.4	0.88
20401.02	29.3	1.15	16.8	0.66	33.4	1.31	348	78	21.4	0.84	12.0	0.47	943	212	18.8	0.74
20402.02	29.3	1.15	16.8	0.66	36.4	1.43	356	80	23.4	0.92	13.0	0.51	1004	226	21.9	0.86
20408.02	29.3	1.15	17.4	0.69	32.2	1.27	316	71	21.7	0.85	10.5	0.41	720	162	18.1	0.71
20411.02	29.4	1.16	16.9	0.67	40.5	1.59	367	82	27.0	1.06	13.5	0.53	1060	238	25.3	1.00
20451.01	29.4	1.16	21.2	0.83	40.5	1.59	295	66	26.5	1.04	14.0	0.55	900	202	24.7	0.97
20460.02	29.4	1.16	16.6	0.65	36.4	1.43	358	80	23.4	0.92	13.0	0.51	1055	237	21.6	0.85
20453.02	29.6	1.17	17	0.67	32.5	1.28	311	70	18.1	0.71	14.4	0.57	1010	227	16.8	0.66
20454.02	29.6	1.17	16.8	0.66	40.0	1.57	309	69	29.0	1.14	11.0	0.43	898	202	23.8	0.94
20406.02	30.2	1.19	17.9	0.70	31.8	1.25	329	74	20.3	0.80	11.5	0.45	840	189	16.1	0.63
20449.01	30.2	1.19	22.6	0.89	36.4	1.43	245	55	23.4	0.92	13.0	0.51	730	164	21.9	0.86
20448.01	30.5	1.20	22.5	0.89	36.5	1.44	300	67	21.5	0.85	15.0	0.59	945	212	20	0.79
20447.02	30.8	1.21	17.3	0.68	31.2	1.23	401	90	18.9	0.74	12.3	0.48	1175	264	16.9	0.67
20415.01	31.2	1.23	22.2	0.87	43.2	1.70	409	92	31.8	1.25	11.4	0.45	950	213	27.5	1.08
20702.02	31.6	1.24	18.1	0.71	36.5	1.44	274	62	25.5	1.00	11.0	0.43	807	181	20.6	0.81
25408.01	31.6	1.24	22.6	0.89	45.7	1.80	600	135	30.5	1.20	14.2	0.56	1282	288	28.2	1.11
20444.02	31.8	1.25	17.3	0.68	36.0	1.42	399	90	23.3	0.92	12.7	0.50	1231	277	20.7	0.81
30011.01	31.8	1.25	21.8	0.86	43.2	1.70	490	110	31.8	1.25	13.5	0.53	1291	290	29.5	1.16
30002.02	31.9	1.25	17.7	0.70	37.0	1.46	549	123	24.0	0.94	13.0	0.51	1297	291	21.1	0.83
20450.02	32.0	1.26	18	0.71	39.2	1.54	339	76	24.2	0.95	15.0	0.59	1090	245	21	0.83
20420.01	34.7	1.37	25.7	1.01	43.2	1.70	449	101	30.5	1.20	12.7	0.50	930	209	24.8	0.98

**EVS Specification Sheet (continued)**

P/N Each	Outer O.D.		Inner I.D.		L1		F1		L2		Max. Lift		F2		Lc	
	mm	inch	mm	inch	mm	inch	N	LBS	mm	inch	mm	inch	N	LBS	mm	inch
20427.01	35.0	1.38	26	1.02	47.3	1.86	560	126	35.6	1.40	11.7	0.46	933	210	27.5	1.08
20425.01	36.0	1.42	26	1.02	41.9	1.65	458	103	30.5	1.20	11.4	0.45	1073	241	27.3	1.07
30006.02	36.1	1.42	20.6	0.81	45.7	1.80	538	121	27.9	1.10	17.8	0.70	1611	362	25.1	0.99
30003.02	38.1	1.50	19.8	0.78	48.3	1.90	1019	229	31.8	1.25	16.5	0.65	2434	547	28.4	1.12
30008.02	38.6	1.52	20.3	0.80	52.1	2.05	846	190	31.8	1.25	20.3	0.80	2599	584	29.7	1.17
30007.01	39.1	1.54	28.4	1.12	48.3	1.90	645	145	34.3	1.35	14.0	0.55	1469	330	31.5	1.24
30001.02	39.9	1.57	21.3	0.84	52.1	2.05	903	203	33.0	1.30	19.1	0.75	2577	579	27.2	1.07
30013.02	39.9	1.57	20.8	0.82	52.1	2.05	832	187	35.6	1.40	16.5	0.65	2430	546	31.8	1.25
30004.02	40.1	1.58	21.3	0.84	49.5	1.95	1081	243	30.5	1.20	19.1	0.75	2790	627	27.4	1.08
30010.02	40.4	1.59	21.3	0.84	52.1	2.05	979	220	31.8	1.25	20.3	0.80	3168	712	29.7	1.17
35003.02	41.1	1.62	18.8	0.74	53.8	2.12	1095	246	33.8	1.33	19.1	0.75	3177	714	29.2	1.15
30005.02	41.3	1.63	21.6	0.85	50.8	2.00	1135	255	31.8	1.25	19.1	0.75	3075	691	28.7	1.13
30012.02	41.3	1.63	21.3	0.84	50.8	2.00	1202	270	31.8	1.25	19.1	0.75	3382	760	29.5	1.16
15001.01	41.9	1.65	27.2	1.07	52.1	2.05	676	152	33.0	1.30	19.1	0.75	1744	392	29.7	1.17

**EVS Part Number System**

XXXXX.01	Single spring
X5XXX.01	Single spring with beehive top or conical shape
XXXXX.02	Double spring
X5XXX.02	Double spring with beehive top or conical shape
XXXXX.104	Engine set with 4 single springs
XXXXX.108	Engine set with 8 single springs
XXXXX.116	Engine set with 16 single springs
XXXXX.124	Engine set with 24 single springs
XXXXX.132	Engine set with 32 single springs
XXXXX.204	Engine set with 4 double springs
XXXXX.208	Engine set with 8 double springs
XXXXX.216	Engine set with 16 double springs
XXXXX.224	Engine set with 24 double springs
XXXXX.232	Engine set with 32 double springs

	PRIX UNITAIRE		PRIX POUR 16 UNITES	
	HT	TTC	HT	TTC
RESSORT SIMPLE	12.85	15.37	205.6	245.9
RESSORT DOUBLE	19.66	23.51	314.52	376.16
RESSORT V8	26.46	31.65	~	~

**Contact Info:**

Jacquemin Tuning  
233 Avenue de la République  
59110 La Madeleine  
France  
Tel : 00 (0) 3 20746480  
Fax : 00 (0) 3 20746489  
[info@jacquemintuning.com](mailto:info@jacquemintuning.com)  
[www.jacquemintuning.com](http://www.jacquemintuning.com)