

Ref.	Alesage	Oversize	Course	Longueur Bielle	Hauteur axe	Volume chambre CC's	C/R avec 1 mm	Dome CC's	Poids	Note	Type Jupe	€ HTVA	€ TTC
HONDA 1993-97 DEL SOL & 1990-00 CIVIC Si B16A1/A2/A3													
189681	81	STD	77.39	134.36	30	42.7	8.0:1	-9.2	268	T	R	171.30	204.87
218900	81	STD	77.39	134.36	30	42.7	8.0:1	-9.2	268	T	F	184.07	220.15
189682	81.5	0.5	77.39	134.36	30	42.7	8.0:1	-9.2	272	T	R	171.30	204.87
218901	81.5	0.5	77.39	134.36	30	42.7	8.0:1	-9.2	273	T	F	184.07	220.15
242878	82	1	77.39	134.36	30	42.7	8.0:1	-8.9	280	T	R	171.30	204.87
242879	83	2	77.39	134.36	30	42.7	8.0:1	-10.2	289	N,T	R	171.30	204.87
185917	84	3	77.39	134.36	30	42.7	8.0:1	-11.9	291	N,T	R	171.30	204.87
199888	84.5	3.5	77.39	134.36	30	42.7	8.0:1	-11.9	292	N,T	R	171.30	204.87
185918	85	4	77.39	134.36	30	42.7	8.0:1	-11.9	296	N,T	R	171.30	204.87
176449	81	STD	77.39	134.36	30	42.7	9.0:1	-1.7	285	T	R	164.05	196.20
218902	81	STD	77.39	134.36	30	42.7	9.0:1	-1.7	286	T	F	184.07	220.15
176450	81.5	0.5	77.39	134.36	30	42.7	9.0:1	-1.7	290	T	R	164.05	196.20
218903	81.5	0.5	77.39	134.36	30	42.7	9.0:1	-1.7	290	T	F	184.07	220.15
185919	84	3	77.39	134.36	30	42.7	9.5:1	-1.7	295	N,V	R	171.30	204.87
185920	85	4	77.39	134.36	30	42.7	9.5:1	-1.7	304	N,V	R	171.30	204.87
209847	84	3	77.39	134.36	30	42.7	10.3:1	3.2	296	N,U	R	171.30	204.87
209848	84.5	3.5	77.39	134.36	30	42.7	10.4:1	3.2	300	N,U	R	171.30	204.87
185922	85	4	77.39	134.36	30	42.7	10.7:1	3.5	318	U	R	171.30	204.87
253036	81	STD	77.39	134.36	30	42.7	11.0:1	8.2	282	V	R	171.30	204.87
253037	81.5	0.5	77.39	134.36	30	42.7	11.0:1	8.2	288	V	R	171.30	204.87
ACURA 1997-2001 INTEGRA TYPE R B18C5													
188982	81.5	0.5	87.2	138	30.35	42.7	9.0:1	-9.8	266	T	R	171.30	204.87
218906	81.5	0.5	87.2	138	30.35	42.7	9.0:1	-9.8	261	T	F	184.07	220.15
209846	81.5	0.5	87.2	138	30.22	42.7	12.0:1	5.3	285	U	R	171.30	204.87
218907	81.5	0.5	87.2	138	30.22	42.7	12.0:1	5.3		U	F	POA	POA
HONDA 2000-2003 S2000 F20C1													
252606	87	STD	84	153	30	50	9.0:1			T	R	POA	POA
252607	87	STD	84	153	30	50	11.5:1			V	R	POA	POA
HONDA 1992-96 PRELUDE Si & 1997-01 PRELUDE H23A1 - (Must sleeve block.)													
208472	87.5	0.5	95	141.5	30.58	50	9.0:1	-12	328	G,T	R	171.30	204.87
253993	88	1	95	141.5	30.58	50	9.0:1	-13	330	G,T	R	171.30	204.87
208474	87.5	0.5	95	141.5	30.58	50	10.0:1	-5.8	316	G,V	R	171.30	204.87
ACURA K24A2 WITH A K20A2 HEAD													
242866	87	STD	99	152	29.87	50.7	8.2:1	-22.7	312	T	R	171.30	204.87
242867	88	1	99	152	29.87	50.7	8.2:1	-24.6	319	N,T	R	171.30	204.87
242869	89	2	99	152	29.87	50.7	8.2:1	-26.1	328	N,T	R	171.30	204.87
242858*	87	STD	99	152	29.87	50.7	10.0:1	-6.3	316	V	R	171.30	204.87
242862*	88	1	99	152	29.87	50.7	10.0:1	-7.6	325	V	R	171.30	204.87
242865*	89	2	99	152	29.87	50.7	10.0:1	-9	335	N,V	R	171.30	204.87
242194*	87	STD	99	152	29.87	50.7	13.3:1	8.6	334	U	R	171.30	204.87
242196*	88	1	99	152	29.87	50.7	13.3:1	8.3	341	U	R	171.30	204.87
242198*	89	2	99	152	29.87	50.7	13.3:1	7.3	347	N,U	R	171.30	204.87

Ref.	Alesage	Oversize	Course	Longueur Bielle	Hauteur axe	Volume chambre CC's	C/R avec 1 mm	Dome CC's	Poids	Note	Type Jupe	€ HTVA	€ TTC
ACURA 1994-01 INTEGRA GSR B18C1													
189681	81	STD	87.2	138	30	41.5	9.0:1	-9.2	268	T	R	171.30	204.87
218900	81	STD	87.2	138	30	41.5	9.0:1	-9.2	269	T	F	184.07	220.15
189682	81.5	0.5	87.2	138	30	41.5	9.0:1	-9.2	272	T	R	171.30	204.87
218901	81.5	0.5	87.2	138	30	41.5	9.0:1	-9.2	273	T	F	184.07	220.15
242878	82	1	87.2	138	29.87	41.5	9.2:1	-8.9	280	N,T	R	171.30	204.87
242879	83	2	87.2	138	29.87	41.5	9.2:1	-10.2	289	N,T	R	171.30	204.87
185917	84	3	87.2	138	30	41.5	9.2:1	-11.9	291	N,T	R	171.30	204.87
199888	84.5	3.5	87.2	138	30	41.5	9.2:1	-11.9	292	N,T	R	171.30	204.87
185918	85	4	87.2	138	30	41.5	9.3:1	-11.9	296	N,T	R	171.30	204.87
242876	82	1	87.2	138	29.87	41.5	10.0:1	-3.6	291	N,T	R	164.05	196.20
242877	83	2	87.2	138	29.87	41.5	10.0:1	-4.8	299	N,T	R	164.05	196.20
176449	81	STD	87.2	138	30	41.5	10.0:1	-1.7	285	T	R	164.05	196.20
218902	81	STD	87.2	138	30	41.5	10.0:1	-1.7	286	T	F	184.07	220.15
176450	81.5	0.5	87.2	138	30	41.5	10.0:1	-1.7	290	T	R	164.05	196.20
218903	81.5	0.5	87.2	138	30	41.5	10.0:1	-1.7	290	T	F	184.07	220.15
242872	81	STD	87.2	138	30	41.5	12.0:1	5.9	275	U	R	171.30	204.87
242873	81.5	0.5	87.2	138	30	41.5	11.7:1	4.1	274	U	R	171.30	204.87
242874	82	1	87.2	138	29.87	41.5	12.0:1	5	275	N,U	R	171.30	204.87
242875	83	2	87.2	138	29.87	41.5	12.0:1	4.1	285	N,U	R	171.30	204.87
242149	81	STD	87.2	138	30.22	41.5	12.5:1	7.4		U	R	171.30	204.87
218904	81	STD	87.2	138	30.22	41.5	12.5:1	7.4		U	F	POA	POA
242150	81.5	0.5	87.2	138	30.22	41.5	12.5:1	7.4	283	U	R	171.30	204.87
218905	81.5	0.5	87.2	138	30.22	41.5	12.5:1	7.4		U	F	POA	POA
HONDA B20 VTEC WITH A B16A HEAD													
185917	84	STD	89	137	30	42.7	9.1:1	-11.6	291	T	R	171.30	204.87
218908	84	STD	89	137	30	42.7	9.1:1	-11.6	279	T	F	184.07	220.15
199888	84.5	0.5	89	137	30	42.7	9.3:1	-11.6	292	T	R	171.30	204.87
218909	84.5	0.5	89	137	30	42.7	9.3:1	-11.6	284	T	F	184.07	220.15
185918	85	1	89	137	30	42.7	9.3:1	-11.6	296	T	R	171.30	204.87
218910	85	1	89	137	30	42.7	9.3:1	-11.6	288	T	F	184.07	220.15
185919	84	STD	89	137	30	42.7	11.0:1	-0.3	295	V	R	171.30	204.87
218911	84	STD	89	137	30	42.7	11.0:1	-0.3		V	F	POA	POA
185920	85	1	89	137	30	42.7	11.2:1	-0.3	305	V	R	171.30	204.87
218912	85	1	89	137	30	42.7	11.2:1	-0.3		V	F	POA	POA
209847	84	STD	89	137	30	42.7	12.0:1	4.2	296	U	R	171.30	204.87
218913	84	STD	89	137	30	42.7	12.0:1	4.2		U	F	POA	POA
209848	84.5	0.5	89	137	30	42.7	12.2:1	4.2	300	U	R	171.30	204.87
218914	84.5	0.5	89	137	30	42.7	12.2:1	4.2		U	F	POA	POA
185922	85	1	89	137	30	42.7	12.1:1	3.5	318	U	R	171.30	204.87
218916	85	1	89	137	30	42.7	12.1:1	3.5		U	F	POA	POA
185921	84	STD	89	137	30	42.7	12.8:1	7	286	U	R	171.30	204.87
218915	84	STD	89	137	30	42.7	12.8:1	7		U	F	POA	POA
185922	85	1	89	137	30	42.7	12.1:1	3.5	318	U	R	171.30	204.87
218916	85	1	89	137	30	42.7	12.1:1	3.5		U	F	POA	POA

Ref.	Alesage	Oversize	Course	Longueur Bielle	Hauteur axe	Volume chambre CC's	C/R avec 1 mm	Dome CC's	Poids	Note	Type Jupe	€ HTVA	€ TTC
HONDA 1992-1996 PRELUDE Si & 1997-01 PRELUDE H22A1 / A4													
208475	87	STD	90.7	143	30.98	53.8	9.0:1	-7.3	325	G,T	R	171.30	204.87
253988	87.5	0.5	90.7	143	30.98	53.8	9.0:1	-7.8	325	G,T	R	171.30	204.87
253990	88	1	90.7	143	30.98	53.8	9.0:1	-8.5	325	G,T	R	171.30	204.87
166036	87	STD	90.7	143	30.98	53.8	10.0:1	0.7	322	G,V	R	171.30	204.87
166035	87	STD	90.7	143	30.98	53.8	12.0:1	11.3	354	G,U	R	171.30	204.87
ACURA 2002-UP RSX TYPE S & 2006 CIVIC Si K20A2/A3													
204255	86	STD	86	138.98	29.87	50.7	9.0:1	-4.7	309	T	R	171.30	204.87
253984	86.5	0.5	86	138.98	29.87	50.7	9.0:1	-4.7	309	T	R	171.30	204.87
204256	86	STD	86	138.98	29.87	50.7	10.8:1	7.1	307	M,V	R	171.30	204.87
226379	86	STD	86	138.98	29.87	50.7	11.3:1	9.2	313	U	R	171.30	204.87
DODGE NEON 2003-UP SRT-4 A853 / SRT4													
240192	87.5	STD	101	151	36.37	52	8.5:1	-20.4	361	T	R	171.30	204.87
240193	88	0.5	101	151	36.37	52	8.5:1	-21.6	364	T	R	171.30	204.87
DODGE NEON 1994-01 ECB / ECC / 420A													
208476	88	0.5	83	138.93	31.4	52	8.8	-3.1	339	T	R	171.30	204.87
242870	88	0.5	83	138.93	31.4	52	10.5:1	8	347	V	R	171.30	204.87
242871	88.5	1	83	138.93	31.4	52	10.5:1	7.6	351	V	R	171.30	204.87
FORD 2000-UP ZX3 ZETEC													
185915	85	0.18	88	139.2	29.74	48	9.0:1	-6.9	299	T	R	171.12	204.66
185916	85	0.18	88	139.2	29.74	48	10.8:1	4.5	321	V	R	171.12	204.66
MAZDA MIATA 1994-2005 BP 1.8 LITER													
255773	83.5	0.5	85	132.95	30.6	50	9.0:1	-2	294	T	R	171.30	204.87
255774	84	1	85	132.95	30.6	50	9.0:1	-2.7	301	T	R	171.30	204.87
255775	84.5	1.5	85	132.95	30.6	50	9.0:1	-3.4	307	T	R	171.30	204.87
MITSUBISHI 1988-92 ECLIPSE / TALON / EVO 4G63 21MM PIN													
208478	85.5	0.5	88	150	34.72	47	8.5:1	-13.2	317	T	R	171.30	204.87
253995	86	1	88	150	34.72	47	8.5:1	-14	319	T	R	POA	POA
202194*	85.5	0.5	100	150	28.7	47	8.5:1	-22	285	T	R	175.72	210.16
202195*	86	1	100	150	28.7	47	8.5:1	-22	292	T	R	175.72	210.16
MITSUBISHI 4G64 WITH 4G63 HEAD 21MM PIN													
256466	87	0.5	100	150	34.72	47	8.5:1	-24		T	R	171.30	204.87
256467	87.5	1	100	150	34.72	47	8.5:1	-24.9		T	R	171.30	204.87
MITSUBISHI 1993-UP ECLIPSE / TALON / EVO 4G63 22MM PIN													
208477	85.5	0.5	88	150	34.72	47	8.5:1	-13.2	316	T	R	171.30	204.87
254006	86	1	88	150	34.72	47	8.5:1	-14	319	T	R	171.30	204.87
202192*	85.5	0.5	100	150	28.7	47	8.5:1	-22	285	T	R	175.50	209.89
202193*	86	1	100	150	28.7	47	8.5:1	-22	286	T	R	175.50	209.89
MITSUBISHI 4G64 WITH 4G63 HEAD 22MM PIN													
256468	87	0.5	100	150	34.72	47	8.5:1	-24		T	R	171.30	204.87
256469	87.5	1	100	150	34.72	47	8.5:1	-24.9		T	R	171.30	204.87
NISSAN 1991-98 240SX KA24DE													
244514	89.5	0.5	96	165	33.94	46	9.0:1	-22.2	355	T	R	171.30	204.87
250642	89.5	0.5	96	165	33.94	46	11.0:1	-6.6	346	V	R	171.30	204.87

Ref.	Alesage	Oversize	Course	Longueur Bielle	Hauteur axe	Volume chambre CC's	C/R avec 1 mm	Dome CC's	Poids	Note	Type Jupe	€ HTVA	€ TTC
NISSAN 2003-UP 350Z & G35 VQ35DE													
231532	95.5	STD	81.4	144.14	29.6	56	8.5:1	-12.6	380	T	R	171.30	204.87
231580	95.5	STD	81.4	144.14	29.6	56	10.5:1	4.7	363	V	R	171.30	204.87
NISSAN SENTRA/200SX SE-R, SILVIA, 180SX & BLUEBIRD SR20DET													
244871	86	STD	86	136.3	31.82	46.5	8.5:1	-11.3	330	T	R	171.30	204.87
245015	86.5	0.5	86	136.3	31.82	46.5	8.5:1	-11.8	334	T	R	171.30	204.87
245016	87	1	86	136.3	31.82	46.5	8.5:1	-12.4	340	T	R	171.30	204.87
NISSAN 1990-1996 300ZX VG30DE(TT)													
165053	87.5	0.5	83	154.2	31.88	49.5	9.0:1	-4.5	348	T	R	171.30	204.87
166027	87.5	0.5	83	154.2	31.88	49.5	11.0:1	7	329	M,V	R	171.30	204.87
NISSAN R32-R34 SKYLINE RB26DETT													
209849	86.5	0.5	86	121.42	30.1	70	8.2:1	15.3	355	T	R	171.30	204.87
209855	87	1	86	121.42	30.1	70	8.2:1	15.3	360	T	R	171.30	204.87
SUBARU 2004+ IMPREZA STI , 2005+ FORESTER XT, LEGACY GT, 2006+ WRX EJ257													
245986	99.5	STD	79	130.48	30.7	50	8.5:1	-21.5	394	T	R	175.50	209.89
256058	100	1	79	130.48	30.7	50	8.5:1	-22.2	400	T	R	177.77	212.62
SUBARU 2002-2005 IMPREZA WRX EJ205													
205090	92	STD	75	130.48	32.69	48	8.5:1	-11.8	364	T	R	175.50	209.89
226378	92.5	0.5	75	130.48	32.69	48	8.5:1	-11.8	371	T	R	175.50	209.89
SUBARU 1997-UP SUBARU IMPREZA , FORESTER, LEGACY EJ25													
205091	99.5	STD	79	130.48	30.27	48	8.2:1	-23	386	T	R	175.50	209.89
205103	99.5	STD	79	131.19	29.51	51	8.5:1	-18.8	387	M,T	R	175.50	209.89
TOYOTA 1993-98 SUPRA TURBO 2JZGTE													
252059	86.5	0.5	86	142	33.98	40	8.5:1	-20.8	330	T	R	171.30	204.87
252060	87	1	86	142	33.98	40	8.5:1	-21.5	333	T	R	171.30	204.87
SCION 2005-UP TC, 2002-UP CAMRY 4CYL, 2002-UP SOLARA 2AZFE													
253054	89	0.5	96	149.5	33	40.2	9.0:1	-27.1	337	T	R	171.30	204.87
253055	89	0.5	96	149.5	33	40.2	11.0:1	-12.2	322	V	R	171.30	204.87
TOYOTA 5SFE BLOCK/ 3SGTE HEAD													
252064	87.5	0.5	91	138	32.51	50	9.0:1	-11.6	338	T	R	171.30	204.87
TOYOTA 1991-95 MR2 TURBO 3SGTE													
252061	86.5	0.5	86	138	35	50	9.0:1	-6.5	351	T	R	171.30	204.87
252062	87	1	86	138	35	50	9.0:1	-7.2	356	T	R	171.30	204.87
TOYOTA 1987-92 SUPRA TURBO 7MGTE													
186241	83.5	0.5	90.98	152	32.74	40	8.8:1	-16.1	296	T	R	171.30	204.87
186242	84	1	90.98	152	32.74	40	8.9:1	-16.1	301	T	R	171.30	204.87
VOLKSWAGEN 1990-93 2.0L 16V JETTA / GTI / PASSAT													
186231	83	0.5	92.81	144	29.81	46	9.5:1	-7.4	286	T	R	171.30	204.87
186232	83.5	1	92.81	144	29.81	46	9.5:1	-7.4	293	T	R	171.30	204.87
186233	83	0.5	92.81	144	29.81	46	11.2:1	2.8	283	V	R	164.05	196.20
186234	83.5	1	92.81	144	29.81	46	11.3:1	2.8	294	V	R	164.05	196.20

Ref.	Alesage	Oversize	Course	Longueur Bielle	Hauteur axe	Volume chambre CC's	C/R avec 1 mm	Dome CC's	Poids	Note	Type Jupe	€ HTVA	€ TTC
VOLKSWAGEN 1993-99 2.0L 8V GOLF III / JETTA III													
186239	82.5	STD	92.81	159	30.81	30	10.2:1	-19.6	257	V	R	171.30	204.87
186240	83	0.5	92.81	159	30.81	30	10.2:1	-19.6	258	V	R	171.30	204.87
VW / AUDI A4, GOLF, JETTA, TT 1.8T													
242909	81	STD	86.41	144	32.66	43	8.5:1	-8.1	296	T	R	194.19	232.25
242926	81.5	0.5	86.41	144	32.66	43	8.5:1	-8.7	304	T	R	194.19	232.25
242928	82	1	86.41	144	32.66	43	8.5:1	-9.3	310	T	R	194.19	232.25
242880	81	STD	86.41	144	32.66	43	9.25:1	-2.7	299	T	R	194.19	232.25
242881	81.5	0.5	86.41	144	32.66	43	9.25:1	-3.1	303	T	R	194.19	232.25
242882	82	1	86.41	144	32.66	43	9.25:1	-3.6	308	T	R	194.19	232.25
VOLKSWAGEN 1992-99 VR6 GTI / JETTA GLX / PASSAT AAA													
186235	82	1	90.22	164	32.38	-	9.0:1	-11.6	304	T	R	171.30	204.87
186236	83	2	90.22	164	32.38	-	9.0:1	-11.6	306	T	R	171.30	204.87
186237	82	1	90.22	164	32.38	-	10.0:1	-5.1	296	V	R	171.30	204.87
186238	83	2	90.22	164	32.38	-	10.0:1	-5.1	302	V	R	171.30	204.87
PORSCHE 911 3.0L													
212435	95	STD	70.4	127.8	34	38.5	9.5	-	417	-	-	201.60	241.11
212436	95	STD	70.4	127.8	34	44.7	10.5	-	431	-	-	201.60	241.11
212437	98	3	70.4	127.8	34	35.2	9.5	-	441	-	-	201.60	241.11
212438	98	3	70.4	127.8	34	41.8	10.5	-	448	-	-	201.60	241.11
PORSCHE 911 3.2L													
212439	95	STD	74.4	127	32.8	35.1	9.5	-	414	-	-	194.55	232.68
212440	95	STD	74.4	127	32.8	41.7	10.5	-	419	-	-	194.55	232.68
212441	98	3	74.4	127	32.8	31.6	9.5	-	434	-	-	194.55	232.68
212442	98	3	74.4	127	32.8	38.6	10.5	-	433	-	-	194.55	232.68
PORSCHE 911 3.6L													
212444	100	STD	76.4	127	31.8	40.8	11.5	-	432	-	-	194.55	232.68
212443	100	STD	76.4	127	31.8	45.8	12.5	-	443	-	-	194.55	232.68
212446	102	2	76.4	127	31.8	38.8	11.5	-	445	-	-	194.55	232.68
212445	102	2	76.4	127	31.8	44	12.5	-	460	-	-	194.55	232.68

Note : T accepts Turbo and Nitrous. V accepts Nitrous. U Not designed for Turbo. M Block must be resleeved. Type : R Full round circle. F Forged side relief.

Be careful, rings are not included

